



TYPE :

AA = Music Wire #SWP-A
AS = Stainless #SUS304-WPB



BA = Music Wire #SWP-A
BS = Stainless #SUS304-WPB




We accept
PayPal & Ship Worldwide
Min. order **10pcs** only

PART NO.				Wire Diameter	Sugg. Max. Deflection	Sugg. Max. Load	Initial Tension	Rate
CATEGORY + TYPE + OUTSIDE DIA. (D) + LENGTH (L)				(d) mm	(F) mm	N	N	N/mm
TSA	AA AS	2	10	0.2	6.7	0.69	0.13	0.083
			15		11.8			0.047
			20		17.2			0.032
			25		22.8			0.025
			30		28.5			0.020
TSA	AA AS	3	10	0.25	10.4	1.27	0.15	0.110
			15		23.0			0.049
			20		35.9			0.031
			25		47.9			0.024
			30		57.5			0.020
TSA	AA AS	4	15	0.35	14.6	2.26	0.25	0.14
			20		24.1			0.083
			25		32.5			0.062
			30		42.7			0.047
			35		51.2			0.039
TSA	AA AS	5	40	0.45	60.3	3.24	0.49	0.033
			15		8.2			0.33
			20		15.5			0.18
			25		21.5			0.13
			30		29.4			0.093
TSA	AA AS	6	35	0.56	35.0	6.08	0.64	0.078
			40		43.0			0.064
			45		50.9			0.054
			50		56.0			0.049
			20		16.2			0.34
TSA	AA AS	8	25	0.7	25.2	8.53	1.08	0.22
			30		34.7			0.16
			35		42.7			0.13
			40		50.4			0.11
			45		61.6			0.088
TSA	AA AS	10	50	0.9	69.3	10.8	2.06	0.079
			55		79.3			0.069
			60		85.3			0.064
			25		18.1			0.41
			30		27.1			0.28
TSA	AA AS	12	35	1.1	36.2	19.6	2.94	0.21
			40		44.7			0.17
			45		54.2			0.14
			50		63.3			0.12
			55		69.0			0.11
TSA	AA AS		60		80.0			0.093
			65		89.4			0.083
			70		95.0			0.078
			30		13.4			0.65
			35		18.5			0.47
TSA	AA AS		40		24.0			0.36
			45		29.6			0.29
			50		35.6			0.25
			55		42.3			0.21
			60		46.8			0.19
TSA	AA AS		70		59.3			0.15
			80		68.4			0.13
			90		80.9			0.11
			100		93.6			0.093
TSA	AA AS		35		17.8			0.94
			40		25.0			0.67
			45		31.0			0.54
			50		37.7			0.44
			55		44.7			0.37
TSA	AA AS		60		51.5			0.32
			70		65.3			0.26
			80		77.2			0.22
			90		94.4			0.18
			100		106.2			0.16


Part Number Example : TSA-AA-8-60

TYPE :

AA = Music Wire #SWP-A
AS = Stainless #SUS304-WPB



BA = Music Wire #SWP-A
BS = Stainless #SUS304-WPB



We accept
PayPal & Ship Worldwide


Min. order 10pcs only

PART NO.				Wire Diameter	Sugg. Max. Deflection	Sugg. Max. Load	Initial Tension	Rate
CATEGORY + TYPE + OUTSIDE DIA. (D) + LENGTH (L)				(d) mm	(F) mm	N	N	N/mm
TSY	AA AS	2	10	0.25	5.7	1.86	0.34	0.27
			15		10.3			0.15
			20		14.0			0.11
			25		18.2			0.08
			30		22.1			0.07
TSY	AA AS BA BS	3	10	0.3	8.7	2.25	0.29	0.23
			15		16.6			0.12
			20		25.0			0.08
			25		33.3			0.06
			30		40.0			0.05
TSY	AA AS BA BS	4	15	0.4	10.0	3.24	0.59	0.26
			20		16.8			0.16
			25		22.5			0.12
			30		28.4			0.09
			35		33.7			0.08
TSY	AA AS BA BS	5	40	0.5	38.5	4.22	0.88	0.07
			15		6.8			0.49
			20		11.7			0.28
			25		17.0			0.20
			30		21.2			0.16
TSY	AA AS BA BS	6	35	0.6	26.1	8.14	1.27	0.13
			40		34.0			0.10
			45		37.7			0.09
			50		42.5			0.08
			20		14.0			0.49
TSY	AA AS BA BS	8	25	0.8	21.2	12.75	2.35	0.32
			30		28.0			0.25
			35		35.0			0.20
			40		41.1			0.17
			45		50.0			0.14
TSY	AA AS BA BS	10	50	1.0	53.8	15.0	3.73	0.13
			55		63.6			0.11
			60		70.0			0.10
			25		15.1			0.69
			30		21.2			0.49
TSY	AA AS BA BS	10	35	0.8	26.5	12.75	2.35	0.39
			40		33.1			0.31
			45		39.2			0.26
			50		46.0			0.23
			55		48.1			0.22
TSY	AA AS BA BS	10	60	1.0	53.0	15.0	3.73	0.20
			65		58.8			0.18
			70		66.2			0.16
			30		11.5			0.98
			35		15.3			0.74
TSY	AA AS BA BS	10	40	1.0	19.8	15.0	3.73	0.57
			45		23.9			0.47
			50		28.7			0.39
			55		32.8			0.34
			60		37.0			0.30
TSY	AA AS BA BS	10	65	1.0	39.6	15.0	3.73	0.29
			70		44.2			0.26
			75		47.9			0.24
			80		52.2			0.22
			90		60.5			0.19
TSY	AA AS	10	100	1.0	71.8	15.0	3.73	0.16


Part Number Example : TSY-AA-8-60

TYPE :

AA = Music Wire #SWP-A
AS = Stainless #SUS304-WPB



BA = Music Wire #SWP-A
BS = Stainless #SUS304-WPB



We accept
PayPal & Ship Worldwide


Min. order 10pcs only

PART NO.				Wire Diameter	Sugg. Max. Deflection	Sugg. Max. Load	Initial Tension	Rate
CATEGORY + TYPE + OUTSIDE DIA. (D) + LENGTH (L)				(d) mm	(F) mm	N	N	N/mm
TSY	AA AS BA BS	12	35	1.2	22.0	31.37	5.39	1.18
			40		27.8			0.93
			45		35.3			0.74
			50		42.0			0.62
			55		50.0			0.52
			60		55.2			0.47
			65		63.0			0.41
			70		69.7			0.37
			75		77.9			0.33
			80		82.8			0.31
			90		91.3			0.29
			100		106.0			0.25
TSY	AA AS	14	40	1.5	15.4	38.24	8.43	1.94
			45		21.0			1.42
			50		25.4			1.17
			55		30.8			0.97
			60		37.0			0.80
			65		43.2			0.69
			70		46.2			0.64
			75		52.8			0.56
			80		58.3			0.51
			90		68.1			0.43
			100		76.4			0.39
			125		91.0			0.33
TSY	AA AS	16	45	1.6 (AA) 1.7 (AS)	15.8	43.15	9.12	2.16
			50		21.0			1.62
			55		25.7			1.32
			60		31.5			1.08
			65		35.8			0.95
			70		40.8			0.83
			75		46.3			0.74
			80		49.6			0.69
			90		60.9			0.56
			100		69.4			0.49
			125		91.3			0.37
			150		115.6			0.29
TSY	AA	18	50	1.8	21.0	52.96	9.81	2.05
			55		26.0			1.66
			60		31.0			1.39
			65		36.0			1.20
			70		42.0			1.03
			75		46.0			0.94
			80		54.0			0.80
			90		66.0			0.65
			100		75.0			0.58
			125		104.5			0.41
			150		132.0			0.33
TSY	AA	20	60	2.0	29.1	78.45	12.75	2.26
			70		41.8			1.57
			80		53.6			1.23
			90		67.0			0.98
			100		78.8			0.83
			125		111.6			0.59
			150		139.5			0.47
			175		167.5			0.39


Part Number Example : TSY-AA-18-80

TYPE :

AA = Music Wire #SWP-A
AS = Stainless #SUS304-WPB



BA = Music Wire #SWP-A
BS = Stainless #SUS304-WPB




We accept
PayPal & Ship Worldwide


Min. order **10pcs** only

PART NO.				Wire Diameter	Sugg. Max. Deflection	Sugg. Max. Load	Initial Tension	Rate	
CATEGORY + TYPE + OUTSIDE DIA. (D) + LENGTH (L)				(d) mm	(F) mm	N	N	N/mm	
TSU	AA AS	2	10	0.28	4.0	2.45	0.49	0.49	
			15		6.7			0.29	
			20		10.0			0.20	
			25		13.3			0.15	
TSU	AA AS BA BS	3	10	0.35	4.6	3.33	0.66	0.59	
			15		9.1			0.29	
			20		14.3			0.19	
			25		19.5			0.14	
			30		24.8			0.11	
TSU	AA AS BA BS	4	15	0.45	7.5	4.81	0.98	0.51	
			20		12.2			0.31	
			25		16.9			0.23	
			30		21.7			0.18	
			35		26.0			0.15	
			40		30.0			0.13	
TSU	AA AS BA BS	5	15	0.55	5.7	6.37	1.37	0.89	
			20		9.8			0.51	
			25		14.2			0.35	
			30		18.9			0.26	
			35		24.3			0.21	
			40		28.3			0.18	
			45		31.9			0.16	
			50		36.4			0.14	
TSU	AA AS BA BS	6	20	0.7	9.6	12.94	1.67	1.18	
			25		14.4			0.78	
			30		20.2			0.56	
			35		28.8			0.39	
			40		30.3			0.37	
			45		34.8			0.32	
			50		41.1			0.27	
			55		44.2			0.25	
			60		50.0			0.23	
TSU	AA AS BA BS	8	25	0.9	10.0	18.63	3.92	1.47	
			30		14.3			1.03	
			35		18.8			0.78	
			40		23.8			0.62	
			45		28.3			0.52	
			50		32.6			0.45	
			55		37.5			0.39	
			60		41.7			0.35	
			65		46.9			0.31	
			70		50.0			0.29	
TSU	AA / AS	10	30	1.1	9.9	23.24	4.71	1.87	
	AA AS BA BS		35		14.0			1.32	
			40		18.0			1.03	
			45		22.2			0.83	
			50		26.3			0.71	
			55		31.5			0.59	
			60		35.7			0.52	
			65		38.6			0.48	
			70		43.0			0.43	
			75		47.3			0.39	
			80		51.0			0.36	
			AA		90			59.0	0.31
			AS		100			67.5	0.27

Part Number Example : TSU-AA-8-60

TYPE :
AA = Music Wire #SWP-A

AS = Stainless #SUS304-WPB

BA = Music Wire #SWP-A

BS = Stainless #SUS304-WPB


We accept

& Ship Worldwide


Min. order 10pcs only

PART NO.				Wire Diameter	Sugg. Max. Deflection	Sugg. Max. Load	Initial Tension	Rate
CATEGORY + TYPE + OUTSIDE DIA. (D) + LENGTH (L)				(d) mm	(F) mm	N	N	N/mm
TSU	AA AS BA BS	12	35	1.4	11.7	47.7	10.49	3.14
			40		15.5			2.35
			45		19.6			1.86
			50		23.3			1.57
			55		28.7			1.27
			60		32.4			1.13
			65		37.3			0.98
			70		41.4			0.88
			75		44.9			0.81
			80		49.7			0.74
			90		57.4			0.64
			100		65.4			0.56
TSU	AA AS	14	40	1.6	12.8	58.84	13.73	3.53
			45		16.7			2.70
			50		21.0			2.16
			55		25.5			1.77
			60		28.7			1.57
			65		32.8			1.37
			70		38.3			1.18
			75		41.8			1.08
			80		46.0			0.98
			90		54.1			0.83
			100		61.3			0.74
			125		83.6			0.54
TSU	AA AS	16	45	1.8 (AA) 1.9 (AS)	13.7	70.61	16.67	3.92
			50		17.7			3.04
			55		22.0			2.45
			60		26.0			2.06
			65		30.5			1.77
			70		34.3			1.57
			75		39.2			1.37
			80		42.3			1.27
			90		50.0			1.08
			100		57.8			0.93
			125		78.7			0.69
			150		100.0			0.54
TSU	AA	18	55	2.0	19.1	81.39	17.65	3.34
			60		23.2			2.75
			65		27.0			2.36
			70		30.9			2.06
			75		36.1			1.77
			80		40.6			1.57
			90		48.1			1.33
			100		56.5			1.13
			125		76.4			0.83
			150		100.0			0.64
			175		160			4.72
TSU	AA	20	60	2.3	22.6	98.07	22.56	3.34
			70		28.5			2.65
			80		36.6			2.06
			90		42.7			1.77
			100		59.2			1.28
			125		77.0			0.98
			150		90.5			0.83
			175		160			4.72
			200		226			3.34
			225		285			2.65
			250		366			2.06
			275		427			1.77
			300		592			1.28
			325		770			0.98
			350		905			0.83


Part Number Example : TSU-AA-18-80

TYPE :

AA = Music Wire #SWP-A
AS = Stainless #SUS304-WPB



BA = Music Wire #SWP-A
BS = Stainless #SUS304-WPB



We accept

PayPal & Ship Worldwide


Min. order 10pcs only

PART NO.				Wire Diameter	Sugg. Max. Deflection	Sugg. Max. Load	Initial Tension	Rate	
CATEGORY + TYPE + OUTSIDE DIA. (D) + LENGTH (L)				(d) mm	(F) mm	N	N	N/mm	
TSS	AA AS	2	10	0.3	3.8	3.53	0.69	0.75	
			15		6.7			0.42	
			20		9.6			0.30	
			25		12.6			0.23	
TSS	AA AS BA BA	3	10	0.40	3.5	4.41	0.88	0.98	
			15		6.0			0.59	
			20		9.0			0.39	
			25		12.0			0.29	
			30		15.6			0.23	
TSS	AA AS BA BA	4	15	0.50	6.5	6.37	1.18	0.78	
			20		10.2			0.49	
			25		13.9			0.39	
			30		17.5			0.29	
			35		20.3			0.26	
			40		24.0			0.22	
TSS	AA AS BA BA	5	15	0.6	5.6	8.53	1.57	1.27	
			20		8.9			0.78	
			25		13.7			0.49	
			30		17.3			0.39	
			35		23.7			0.29	
			40		24.5			0.28	
			45		28.4			0.25	
			50		32.2			0.22	
TSS	AA AS BA BA	6	20	0.8	6.7	17.26	3.53	2.06	
			25		9.3			1.47	
			30		12.7			1.08	
			35		15.6			0.88	
			40		18.7			0.69	
			45		20.6			0.68	
			50		24.5			0.57	
			55		28.0			0.50	
			60		29.7			0.47	
TSS	AA AS BA BA	8	25	1.0	9.1	24.52	4.9	2.16	
			30		12.5			1.57	
			35		15.4			1.27	
			40		19.2			0.98	
			45		22.2			0.88	
			50		25.0			0.78	
			55		28.6			0.70	
			60		33.3			0.60	
			65		36.3			0.55	
			70		40.0			0.50	
TSS	AA AS BA BA	10	30	1.2	10.4	30.99	5.49	2.45	
			35		13.7			1.86	
			40		17.3			1.47	
			45		20.0			1.27	
			50		24.8			0.98	
			55		28.2			0.88	
			60		31.6			0.78	
			65		34.2			0.76	
			70		38.8			0.67	
			75		43.3			0.60	
			80		47.2			0.55	
			AA		100			52.0	0.49
			AS					59.0	0.43


Part Number Example : TSS-AA-8-60

TYPE :

AA = Music Wire #SWP-A
AS = Stainless #SUS304-WPB



BA = Music Wire #SWP-A
BS = Stainless #SUS304-WPB



We accept
PayPal & Ship Worldwide


Min. order 10pcs only

PART NO.				Wire Diameter	Sugg. Max. Deflection	Sugg. Max. Load	Initial Tension	Rate
CATEGORY + TYPE + OUTSIDE DIA. (D) + LENGTH (L)				(d) mm	(F) mm	N	N	N/mm
TSS	AA AS BA BA	12	35	1.6	8.5	62.76	14.71	5.69
			40		11.8			4.12
			45		14.3			3.33
			50		16.8			2.84
			55		19.3			2.45
			60		22.3			2.16
			65		24.5			1.96
			70		27.2			1.77
			75		28.8			1.67
			80		32.7			1.47
			90		36.3			1.35
			100		41.0			1.20
TSS	AA AS	14	40	1.8	10.2	74.53	16.67	5.69
			45		13.1			4.41
			50		16.4			3.53
			55		19.7			2.94
			60		21.1			2.75
			65		24.6			2.35
			70		27.6			2.06
			75		31.1			1.86
			80		32.8			1.77
			90		37.5			1.60
			100		42.8			1.40
			125		60.0			1.00
TSS	AA AS	16	45	2.0 (AA) 2.1 (AS)	11.7	86.3	19.61	5.69
			50		15.1			4.41
			55		17.4			3.82
			60		21.3			3.14
			65		23.4			2.84
			70		26.8			2.45
			75		29.6			2.26
			80		32.7			2.10
			90		37.8			1.77
			100		45.3			1.47
			125		56.7			1.20
			150		71.5			0.95
TSS	AA	18	50	2.3	12.5	115.72	27.46	7.06
			55		15.0			5.88
			60		17.3			5.10
			65		20.0			4.41
			70		22.5			3.92
			75		25.0			3.53
			80		29.0			3.04
			90		33.6			2.65
			100		39.1			2.26
			125		53.0			1.70
			150		64.2			1.40
TSS	AA	20	60	2.6	14.7	150.04	36.28	7.75
			70		20.0			5.69
			80		25.2			4.51
			90		30.8			3.73
			100		36.1			3.14
			125		48.3			2.35
			150		59.5			1.95
			175		72.5			1.60
TSS	AA	24	70	3.2	14.7	225.6	56.88	11.47
			80		20.7			8.14
			90		24.9			6.77
			100		29.7			5.69
			125		41.0			4.12
			150		50.6			3.40
			175		61.4			2.80
			200		74.7			2.30


Part Number Example : TSS-AA-18-80

TYPE :

AA = Music Wire #SWP-A
AS = Stainless #SUS304-WPB



BA = Music Wire #SWP-A
BS = Stainless #SUS304-WPB



We accept
PayPal & Ship Worldwide

Min. order **10pcs** only


PART NO.				Wire Diameter	Sugg. Max. Deflection	Sugg. Max. Load	Initial Tension	Rate
CATEGORY + TYPE + OUTSIDE DIA. (D) + LENGTH (L)				(d) mm	(F) mm	N	N	N/mm
TSF	AA	3	10	0.45	2.2	6.47	1.57	2.26
			15		4.5			1.08
			20		6.7			0.74
			25		9.1			0.54
			30		11.4			0.43
TSF	AA	4	15	0.55	4.5	8.43	1.86	1.47
			20		7.1			0.93
			25		10.0			0.66
			30		12.6			0.52
			35		15.2			0.43
TSF	AA	5	40	0.7	18.1	14.71	2.45	0.36
			15		3.9			3.14
			20		6.9			1.77
			25		9.6			1.28
			30		12.5			0.98
TSF	AA	6	35	0.9	15.6	23.54	5.88	0.78
			40		19.2			0.64
			45		21.9			0.56
			50		25.0			0.49
			20		3.9			4.51
TSF	AA	8	25	1.1	6.0	31.38	6.86	2.94
			30		7.8			2.26
			35		10.0			1.77
			40		12.0			1.47
			45		13.8			1.28
TSF	AA	10	50	1.4	16.4	49.03	12.75	1.08
			55		18.0			0.98
			60		20.0			0.88
			25		5.8			4.23
			30		8.3			2.94
TSF	AA	12	35	1.8	10.9	83.36	23.54	2.26
			40		13.2			1.86
			45		15.6			1.57
			50		18.5			1.32
			55		21.7			1.13
TSF	AA		60		23.8			1.03
			65		26.3			0.93
			70		27.8			0.88
			30		6.5			5.58
			35		8.7			4.17
TSF	AA		40		10.7			3.39
			45		12.9			2.81
			50		15.2			2.39
			55		17.2			2.11
			60		19.5			1.86
TSF	AA		70		23.1			1.57
			80		27.4			1.32
			90		32.1			1.13
			100		46.2			0.79
TSF	AA		35		5			12.00
			40		7			8.55
			45		9			6.65
			50		11.0			5.44
			55		13.0			4.60
TSF	AA		60		14.5			4.13
			70		17.8			3.36
			80		21.3			2.81
			90		24.5			2.44
			100		27.5			2.18

Part Number Example : TSF-AA-8-60

TYPE :


AA = Music Wire #SWP-A

AS = Stainless #SUS304-WPB



BA = Music Wire #SWP-A

BS = Stainless #SUS304-WPB



We accept

& Ship Worldwide


Min. order 10pcs only

PART NO.				Wire Diameter	Sugg. Max. Deflection	Sugg. Max. Load	Initial Tension	Rate
CATEGORY + TYPE + OUTSIDE DIA. (D) + LENGTH (L)				(d) mm	(F) mm	N	N	N/mm
TST	AA	3	10	0.5	2.0	8.8	2.16	3.24
	AS		15		3.7			1.77
	BA		20		5.2			1.27
	BS		25		6.8			0.98
	AA / AS		30		8.5			0.78
TST	AA	4	15	0.6	4.0	11.1	2.55	2.16
	AS		20		6.4			1.37
	BA		25		8.4			0.98
	BS		30		10.9			0.78
	AA / AS		35		12.4			0.69
TST	AA AS BA BS	5	40	0.8	15.0	20.79	5.1	0.57
			15		2.9			5.39
			20		4.6			3.43
			25		6.4			2.45
			30		8.4			1.86
	AA AS		35		10.0			1.57
			40		11.4			1.38
			45		13.3			1.18
			50		15.2			1.03
TST	AA AS BA BS	6	20	1.0	3.7	33.15	8.6	6.57
			25		5.3			4.61
			30		6.9			3.53
			35		8.3			2.94
			40		10.0			2.45
	AA AS		45		10.8			2.27
			50		12.5			1.96
			55		14.3			1.71
			60		15.6			1.57
TST	AA AS BA BS	8	25	1.2	5.3	41.19	9.81	5.88
			30		7.3			4.31
			35		9.1			3.43
			40		11.9			2.65
			45		13.6			2.35
	AA AS		50		15.5			2.06
			55		16.8			1.87
			60		18.8			1.67
			65		20.6			1.52
TST	AA AS BA BS	10	70	1.6	22.8	77.47	20.59	1.38
			30		5.2			10.89
			35		6.8			8.34
			40		8.4			6.77
			45		10.0			5.69
			50		11.6			4.90
			55		13.2			4.31
			60		15.2			3.73
	AA AS		65		17.0			3.35
			70		19.3			2.95
			75		20.7			2.75
	80	24.1	2.36					
	90	26.3	2.16					
	100	29.0	1.96					


Part Number Example : TST-AA-8-60

TYPE :

AA = Music Wire #SWP-A
AS = Stainless #SUS304-WPB



BA = Music Wire #SWP-A
BS = Stainless #SUS304-WPB



We accept
PayPal & Ship Worldwide

Min. order **10pcs** only

PART NO.				Wire Diameter	Sugg. Max. Deflection	Sugg. Max. Load	Initial Tension	Rate
CATEGORY + TYPE + OUTSIDE DIA. (D) + LENGTH (L)				(d) mm	(F) mm	N	N	N/mm
TST	AA AS BA BS	12	40	2.0	6.6	120.62	34.3	13.04
			45		7.7			11.18
			50		9.4			9.22
			55		10.5			8.24
			60		12.1			7.16
			65		13.1			6.57
			70		14.9			5.79
			75		16.0			5.39
			80		17.6			4.90
			90		19.1			4.52
TST	AA	14	100	2.3	22.0	154.95	45.11	3.92
			40		5.8			19.02
			45		7.0			15.59
			50		8.4			13.14
			55		9.6			11.47
			60		10.9			10.10
			65		12.9			8.53
			70		14.2			7.75
			75		15.3			7.16
			80		16.7			6.57
TST	AA	16	90	2.6	18.6	195.15	55.9	5.91
			100		21.1			5.21
			125		28.0			3.92
			50		7.5			18.63
			55		9.0			15.49
			60		10.4			13.34
			65		11.9			11.67
			70		13.4			10.40
			75		15.0			9.32
			80		16.5			8.43
TST	AA	18	90	2.9	19.4	236.34	68.85	7.16
			100		22.4			6.18
			125		28.4			4.90
			150		35.5			3.92
			55		8.3			20.10
			60		10.0			16.67
			65		11.6			14.71
			70		12.5			13.44
			75		14.1			11.77
			80		15.8			10.79
TST	AA	20	90	3.2	18.4	281.45	82.38	9.12
			100		21.6			7.15
			125		27.1			6.19
			150		34.2			4.90
			60		9.2			21.57
			70		11.9			16.67
			80		14.7			13.53
			90		17.5			11.38
TST	AA	24	100	4.0	20.1	430.51	123.6	9.90
			125		27.8			7.16
			150		33.8			5.89
			175		40.6			4.90
			80		11.7			26.48
			90		13.7			22.46
			100		16.6			18.63
TST	AA	24	125	4.0	22.5	430.51	123.6	13.63
			150		28.5			10.79
			175		34.4			8.92
			200		41.2			7.45
			80		11.7			26.48

Part Number Example : TST-AA-18-80
